

IDENTIFICATION CODE ARGAL Diaphragm Pump Model DDE 160 ALN YTAGLL

RANGE	MODEL		MATERIALS										CONNECTIONS CONFIGURATION							
			CHAMBERS		VERSION		DIAPHRAGM		BALLS		SEATS		O-RING		TYPE		SUCTION		DISCHARGE	
DDE	160		WR		N		Y		T		P		V		G		L		L	
	030	G 1/2"	WR	PP+GFR	N	STD	M	TPV (**)	T	PTFE	P	PP	D	EPDM	G	BSP THREADS	L	SX	L	SX
	060	G 1/2"	FC	PVDF+CF	X	ATEX			S	AISI 316L	K	PVDF	V	FKM	N	NPT THREADS	R	DX	R	DX
	100	G 1"	AL	AL			H	TPE (***)	D	EPDM	S	AISI 316L	T	PTFE	I	ISO FLANGE	F	FRONT CENTER	F (*1)	FRONT CENTER
	160	G 1"	SS	AISI 316L					N	NBR	A	AL	N	NBR	A	ANSI FLANGE	B	BACK CENTER	B	BACK CENTER
	400	G 1"1/2	SP	AISI 316L ELECTROPOLISHED							Z	PE UHMW			C	CLAMP (*)	V	TOP CENTER	V	TOP CENTER
	650	G 2"					Y	TPE+PTFE									X	SPLITTED	X	SPLITTED

(*) only configuration SPN/SPX

(**) commercial designation: Santoprene® (ExxonMobil), Geolast® (ExxonMobil)

(*1) not recommended

(***) commercial designation: Keyflex® (LG Chem Ltd.), Hytre® (LG Chem Ltd.)